

44 RU ERK Series Rack, 25 Inches Deep, Configured for AV **SKU: ERK-4425-AV**



An economical standalone rack with solid sides, the ERK Series can also be ganged to create partitioned multi-bay installations for thermal management control, and security. It is seismically certified to protect your components when installed with ERK-Z4 brackets.

- 44RU and 25" Deep
- Fully welded construction for maximum strength
- Rack sides include top and bottom venting
- Convenient lacing points and slotted rail brackets for cable management
- Standard front and rear adjustable 10-32 threaded rackrail with numbered spaces
- Includes standard configurable rear door and solid front door
- Comes configured with integrated fan top, vent blockers, and rear door vent
- Includes (1) LACE-OP lacer strip, (4) straight and (2) offset lacer bars and (12) Velcro straps
- Includes (1) PDT-2020C-NS corded power strips (20A, 20 outlet) corded power strip
- Includes (100) 10-32 threaded rack screws

Specifications

Dimensions &

Measurements

CFM	285
Depth	25 in (63.5 cm)
Height	81.13 in (206.1 cm)
Panel Width	19 in (48.3 cm)
Rack Units	44 RU
Shipping Weight	190 lbs (86.2 kg)
UL Load Capacity	2500 lbs (1,134 kg)
Usable Depth	23.47 in (59.6 cm)
Usable Height	77.13 in (195.9 cm)
Width	22 in (55.9 cm)

Characteristics & Features

Color	Black
Federal Ops Country of Origin	USA
Finish	Black Wrinkle Powder Coat
Material	Steel
Product Configuration	Pre-Configured for Pro AV
Rack Rail Type	10-32
Rack Type	Pre-Configured
Rear Door	Yes
Seismic Rated	Yes
Ships Flat	No
UPC	656747095160

Certifications & Warranties

Certifications

ASCE

Seismic Load Capacity

591 lbs (268.1 kg)

Source: https://www.legrandav.com/products/racks/floor_standing/erk_av_rack/erk-4425-av