

---

**Select Series PDU with RackLink, 4 Outlet SKU: RLNK-415R**

---



Monitor your power anytime, anywhere, and even automatically. Select Series PDUs with RackLink™ creates a simple and cost-effective solution that puts intelligent control of power distribution at your fingertips, wherever you are. The applications are endless - RackLink™ allows you to manage everything from a network of digital signage installs, to a building full of conference rooms, to an entire campus of classrooms - all from your device. Plug it in, feel confident, and simply focus on creating an amazing AV experience.

**Control Concepts Supported Product**

Have the confidence that Crestron Certified Modules and Q-SYS Certified Plug-ins for RackLink enabled products are developed and backed by Control Concepts, the premier software developer for the AV industry.

---

Select Series PDUs with RackLink™ Features & Benefits

- **Connect to the free RackLink Cloud!** Monitor and manage all deployed RackLink-enabled Select PDUs around the globe from a single, customizable dashboard.
  - Industry-leading network security and support of IT protocols for demanding end users
    - SSH
    - HTTPS
    - Self-signed certificates
  - 15 Amps
  - 4 Outlets
  - **Oh Snap! It's Compact!** The compact design of this PDU is perfect for "behind-the-display" applications, especially digital signage.
  - **The control you need to maintain the uptime of your equipment.** After you go through the easy set-up of the RackLink™ user interface, you'll have individual IP outlet control for 4 outlets.
  - **Manage the start-up or shut down of your equipment.** RackLink™ enables remote sequencing with user selectable delays for an optimal start-up or shut down progression.
  - **Protect your equipment.** Each PDU comes with basic surge to protect your devices from harmful power anomalies.
  - **Fast and easy commissioning.** Using the RackLink™ Discovery app on iPhone or Android, quickly connect your RackLink™ enabled PDUs and monitor your system, anywhere, anytime.
  - **Automate it and fugetaboutit.** Improve your system reliability by automating actions such as multiple IP AutoPing and recovery.
  - **Always be informed.** Receive automatic notifications of connection status.
  - **Do you prefer to use a third party software?** Seamlessly interfaces with 3rd party AV control systems and cloud platforms for scheduling, control, reporting and even customization.

## Specifications

---

## Dimensions & Measurements

Amps	15 Amp
Cord Length	9 ft (2.7 m)
Depth	9.67 in (24.6 cm)
Height	1.74 in (4.4 cm)
Shipping Weight	6.5 lbs (3 kg)
Width	8.76 in (22.3 cm)

## Characteristics & Features

Available Internationally	No
Cable Type	IEC
Finish	Powder Coat
Mounting Style	Compact
Number of Circuits	1
Outlet Control Type	4
Outlet Count	4
Plug Type	5-15P
Surge Protection Type	Basic
TAA Compliant	No
UPC	656747275302

## Certifications & Warranties

Certifications	ETL Listed
----------------	------------

Source:

[https://www.legrandav.com/products/power/intelligent\\_power/select\\_pdu\\_with\\_racklink/rlnk-415r](https://www.legrandav.com/products/power/intelligent_power/select_pdu_with_racklink/rlnk-415r)