

## NEXSYS™ 6 Outlet, 15 Amp Compact Power with Multi-Stage Surge Protection **SKU: PDX-615C**

---



- 15A with (6) NEMA 5-15R Outlets
- **Oh Snap! It's Compact!** The compact design of this NEXSYS PDU is perfect for "behind-the-display" applications, especially digital signage.
- **It's very flexible.** The NEXSYS Compact PDU includes (2) mounting options for mounting flexibility, a clamp and L-brackets.
  - Easily attach both mounting solutions to a Lever Lock™ plate for tool-free mounting inside a rack, kiosk, in-wall box, etc.
- Multi-stage MOV surge protection
  - 3 stages of surge protection
  - Visual Indicators of surge status on the front and side of the PDU
- **Worried about the under/over voltage? Don't.** With the selectable on/off voltage protection from the dry contact port, it gives the option to protect sensitive equipment from over/under voltage scenarios.
  - If the voltage protection is on and an over or under voltage event happens the outlets will automatically be turned off to protect the equipment. Once the power restores within the acceptable voltage range the PDU will automatically turn the outlets back on.
- **IEC Inlet:** Allows for cleaner cable management by selecting your desired length of power cord.
  - A standard 2' cord is included with all models
- **Tired of blocked outlets?** You pay for 6 outlets and we think you should be able to use all 6 outlets! The outlets are oriented for easier plugging of DC transformers (wall warts) eliminating blocked outlets.

## Specifications

---

## Dimensions & Measurements

|                   |                   |
|-------------------|-------------------|
| AC Voltage Input  | 120 VAC           |
| AC Voltage Output | 120 VAC           |
| Amps              | 15 Amp            |
| Cord Length       | 2 ft (0.6 m)      |
| Depth             | 7 in (17.8 cm)    |
| Height            | 1.74 in (4.4 cm)  |
| Rack Units        | 0 RU              |
| Shipping Weight   | 4.52 lbs (2.1 kg) |
| Width             | 8.15 in (20.7 cm) |

## Characteristics & Features

|                       |                 |
|-----------------------|-----------------|
| Isolated Ground       | No              |
| Outlet Count          | 6               |
| Plug Type             | NEMA 5-15P      |
| Receptacle Type       | NEMA 5-15R      |
| Special Features      | NEXSYS PDU      |
| Surge Protection Type | Multi-Stage MOV |
| TAA Compliant         | No              |
| UPC                   | 656747396427    |

## Certifications & Warranties

|                |           |
|----------------|-----------|
| Certifications | UL Listed |
| Warranty       | 3 years   |

Source:

[https://www.legrandav.com/products/power/compact\\_power/nexsys\\_compact\\_power\\_multi-stage\\_surge\\_protection/PDX-615C](https://www.legrandav.com/products/power/compact_power/nexsys_compact_power_multi-stage_surge_protection/PDX-615C)