

Select Series PDU with RackLink, 9 Outlet 20A **SKU: RLNK-920R**



Monitor your power anytime, anywhere, and even automatically. Select Series PDUs with RackLink™ creates a simple and cost effective solution that puts intelligent control of power distribution at your fingertips, wherever you are. The applications are endless - RackLink™ allows you to manage everything from a network of digital signage installs, to a building full of conference rooms, to an entire campus of classrooms - all from your device. Plug it in, feel confident, and simply focus on creating an amazing AV experience.



Control Concepts Supported Product

Have the confidence that Crestron Certified Modules and Q-SYS Certified Plug-ins for RackLink enabled products are developed and backed by Control Concepts, the premier software developer for the AV industry.

RackLink Select Features & Benefits

- **Connect to the free RackLink Cloud!** Monitor and manage all deployed RackLink-enabled Select PDUs around the globe from a single, customizable dashboard.
 - Industry-leading network security and support of IT protocols for demanding end users
 - SSH
 - HTTPS
 - Self-signed certificates
 - 20 Amps
 - 9 Outlets
- **The control you need to maintain the uptime of your equipment.** After you go through the easy set-up of the RackLink™ user interface, you'll have individual IP outlet control for 4 outlets.
- **Manage the start-up or shut down of your equipment.** RackLink™ enables remote sequencing with user selectable delays for an optimal start-up or shut down progression.
- **Protect your equipment.** Each PDU comes with basic surge to protect your devices from harmful power anomalies.
- **Fast and easy commissioning.** Using the RackLink™ Discovery app on iPhone or Android, quickly connect your RackLink™ enabled PDUs and monitor your system, anywhere, anytime.
- **Automate it and forget about it.** Improve your system reliability by automating actions such as multiple IP AutoPing and recovery.
- **Always be informed.** Receive automatic notifications of connection status.
- **Do you prefer to use a third party software?** Seamlessly interfaces with 3rd party AV control systems and cloud platforms for scheduling, control, reporting and even customization.

Specifications

Dimensions & Measurements

Amps	20 Amp
Cord Length	9 ft (2.7 m)
Depth	9.67 in (24.6 cm)
Height	1.74 in (4.4 cm)
Shipping Weight	11.02 lbs (5 kg)
Width	17.36 in (44.1 cm)

Characteristics & Features

Available Internationally	No
Cable Type	IEC
Finish	Powder Coat
Mounting Style	Rackmount
Number of Circuits	1
Outlet Control Type	8
Outlet Count	9
Plug Type	5-20P
Surge Protection Type	Basic
UPC	656747395505

Certifications & Warranties

Certifications	ETL Listed
----------------	------------

Source:

https://www.legrandav.com/products/power/intelligent_power/select_pdu_with_racklink/rlnk-920r