



## KAC-CAM-360

360° Center table conference camera

---



A 360° conference camera with AI-powered video and audio optimization, perfect for spaces ranging from small huddle rooms to medium-sized meeting rooms. The KAC-CAM-360 is a sleekly designed, high-performance conference camera that transforms hybrid meetings into compact settings. Featuring 4 high-resolution 4K lenses creating a 360° field of view, a built-in powerful 8W speaker system, and 4 integrated microphones, the KAC-CAM-360 ensures crystal-clear communication and immersive engagement for all participants.

Placed at the center of the table, the KAC-CAM-360 delivers enhanced picture quality by positioning the sensor closer to participants for a more natural viewing angle compared to traditional front-of-room cameras. With its panoramic mode and advanced AI features such as Speaker Tracking, Auto Framing, and Smart Gallery, it captures every detail and interaction, ensuring remote participants stay fully engaged. Controlled via Kramer's KAC-TCH-10 MTR Room Controller, the KAC-CAM-360 elevates the meeting experience for everyone, both in-room and remote

### FEATURES

---

- Exceptional image clarity via 4 hi-resolution lenses, each with a 5M pixel camera, delivering a 360° field of view
- Ultra-high-resolution, high-quality 4K video at 30fps
- AI-powered features such as voice tracking, smart gallery, and panoramic mode for a dynamic and engaging meeting experience
- Seamless integration: Works flawlessly with MTR devices, for a streamlined video conferencing experience



## TECHNICAL SPECIFICATIONS

---

|                             |                                                                                                                                           |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor Specifications | 1/2.7"                                                                                                                                    |
| Effective Pixels            | 5M                                                                                                                                        |
| Maximum frame rate          | 30fps                                                                                                                                     |
| Camera                      | Quantity 4<br>Focal length 2.49mm<br>Aperture F/2.5<br>Field of view HFOV360°                                                             |
| Microphone                  | Quantity 4<br>Signal to noise ratio 63dB<br>Pickup range 3m<br>Pickup angle 360° (H)<br>Response frequency 100Hz~8kHz                     |
| Speaker                     | Quantity 1<br>Rated power 8W<br>Sound pressure level 1m ≥ 75dBSPL @pink noise<br>Signal to noise ratio ≥75dB<br>Distortion ≤5%            |
| Power                       | Power supply 12V3A<br>Maximum power consumption 24W                                                                                       |
| I/O                         | USB 3.0 Type-C 1                                                                                                                          |
| General                     | Dimension L x H x D 84.5 × 84.5 × 274.9mm<br>Net weight 0.8kg<br>Accessories USB cable ×1, Remote control ×1, Adapter ×1, Adapter plug ×5 |
| Product Dimensions          | 46.00cm x 9.70cm x 7.30cm (18.11" x 3.82" x 2.87" ) W, D, H                                                                               |
| Product Weight              | 1.1kg (2.3lbs) approx                                                                                                                     |
| Shipping Dimensions         | 53.00cm x 16.50cm x 15.70cm (20.87" x 6.50" x 6.18" ) W, D, H                                                                             |
| Shipping Weight             | 2.4kg (5.2lbs) approx                                                                                                                     |