



C2G

**15ft (4.5m) C2G Performance Series Ultra Flexible High Speed HDMI™ Cable - 4K 60Hz In-Wall, CMG (FT4) Rated**

Part No. AVD\_CG\_C2G10400



C2G Performance Series Ultra Flexible High Speed HDMI™ Cables extend signals over a high-performance HDMI™ cable and support HDMI™ audio and video features including 4K Ultra HD.

These cables are perfect for connecting a wide variety of devices from computers to projectors and monitors, AV presentation furniture, or in-wall applications requiring high speed HDMI™ features and video resolutions up to 4K (4096 x 2160) at 60Hz - perfect for conference rooms, classrooms, houses of worship, and other commercial installations.

This Ultra Flexible High Speed HDMI™ Cable was designed for installations in tight spaces and offers commercial grade connectors that feature compact overmolding for high density environments, integrated finger grips on the top, bottom, and sides, for easy insertion and removal, and the gripping connector shell has 2x greater port retention to keep your devices connected. The gold plated connectors on the cable allow for better shielding, increased electrical conductivity, and durability.

## Features & Benefits

Supports output resolutions up to 4K (4096 x 2160) at 60Hz, delivering high-quality video for clear and detailed screen content

Integrated finger grips on the connectors for easy insertion and removal

Gold-plated connectors for increased electrical conductivity and enhanced durability

Backed by a Lifetime Warranty for peace of mind

In-wall (CMG/FT4) rated jacket, so you can safely run the cable inside of a wall and have a clutter-free, clean look

Gripping connector shell for 2x greater port retention

Supports CEC extensions for control of consumer electronics devices through a single control point

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120104001	Country Of Origin	China
Features	Gripping Connectors	Application Sector	Commercial
Warranty Type	Lifetime	Type	HDMI Cable

### Dimensions

Product Weight US	0.318 kg	Product Length US	15.0 FT
Cable Length	15 ft		

### Listing Agencies / 3rd Party Agencies

CE Certified	Yes	REACH Compliant	Yes
--------------	-----	-----------------	-----

### Additional Information

RoHS Compliant	Yes
----------------	-----

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Operating Temperature Min	-20 °C
-----------------	--------------------------	---------------------------	--------

Wire Gauge	28 AWG	Video Resolution	4K 60Hz
Storage Humidity	85% RH (Non-Condensing)	Plating Specification	Gold
Jacket Application	In-Wall Rated	Bend Radius	90 mm
Signal Transmission	Bidirectional	Operating Temperature Max	76 °C
Cable Type	High Speed HDMI, Ultra-Flexible	Jacket Rating	CL2 Rated, CMG Rated, FT4 Rated
Cable Diameter	7.3 mm	Data Transfer Rate	18 Gbps
Connector 2	HDMI Male	Connector 1	HDMI Male
Video Output Support	HDMI	Operating Temperature	-20°-75°C
Operating Humidity	85% RH (Non-Condensing)	Video Input Support	HDMI
Conductor Material	Copper	Storage Temperature	-10° - 55° C