

## 10ft (3m) USB-C® to HDMI® Audio/Video Adapter Cable - 4K 30Hz **SKU: CG26896**

---



The USB-C to HDMI Audio/Video Adapter Cable 4K 30Hz allows for a direct connection of a USB-C device to an HDTV, projector, or other display with an HDMI port-- making it an ideal solution for the office, work space applications or home use. This adapter cable is a perfect accessory for Apple®, Microsoft® Surface®, and other leading laptops and tablets.

The cable form factor of this adapter provides a simple and convenient solution that eliminates the need for a separate adapter and cable.

This adapter utilizes the audio/video support built into USB Type-C ports to feed an audio/video signal to an HDMI HDTV or projector. This adapter supports up to a 4K (4096 x 2160 at 30Hz) resolution, allowing it to deliver a high quality video image to the connected display.

### Features and Benefits

- Supports resolutions up to 4K (4096 x 2160 at 30Hz)
- Adapter in cable form factor
- Compatible with 3.1 USB-C and Thunderbolt™ 3 ports
- Reversible, symmetrical USB-C connector
- Plug and Play—no driver required
- Compatible with the Apple® iPad Pro®, MacBook®, MacBook Air®, and MacBook Pro®
- Compatible with the Microsoft® Surface® Book 2 and Surface Go

### Electrical Specifications

- USB Type-C OD:3.9MM, Black
- Rated Temperature: 80°C
- Voltage: 30V
- Max Conductor Resistance at 20°C: 34AWG , 860 OHMS/KM
- Insulation Resistance: 10M-KM MIN at 20°C DC 500V. (EIA—364—21)
- Dielectric Strength: AC 500V/1 Minute No Breakdown. (EIA—364—20)

### Physical Specifications

- Operating Temperature: 0 ~ 45°C Ambient
- Storage Temperature: -10 ~ 70°C Ambient
- USB Type-C Male: Contacts Terminal Gold Flash, Nickel Plated Shell; Black Insulation
- HDMI Male: Contacts Terminal Gold Flash, Nickel Plated Shell; Black Insulation. Chipset: PS171 QFN-56
- Molding Material: Black PVC Conforms RoHS
- Product is CE Marked and Conforms to 2011/65/EU RoHS2

## Specifications

---

## Dimensions &

## Measurements

Bend Radius	1.65 in (42 mm)
Cable Diameter	0.17 in (4.2 mm)
Cable Length	10 ft (3.1 m)
Operating Humidity Max	85% RH (Non-Condensing)
Operating Humidity Min	15% RH (Non-Condensing)
Operating Temperature	32° - 113°F (0° - 45°C)
Shipping Weight	0.3 lbs (0.1 kg)
Storage Humidity Max	85% RH (Non-Condensing)
Storage Humidity Min	15% RH (Non-Condensing)
Storage Temperature Max	158 Fahrenheit (70 Celsius)
Storage Temperature Min	14 Fahrenheit (-10 Celsius)
Wire Gauge	34

---

## Characteristics & Features

Application	<ul style="list-style-type: none"><li>• Commercial</li><li>• Residential</li></ul>
Color	Black
Connector 1	<ul style="list-style-type: none"><li>• (1) USB-C Male</li><li>• (1) USB-C Male</li></ul>
Connector 2	<ul style="list-style-type: none"><li>• (1) HDMI Male</li><li>• (1) HDMI Male</li></ul>
Product Type	<ul style="list-style-type: none"><li>• Adapter</li><li>• Cable</li></ul>
TAA Compliant	No
Video Input Support	<ul style="list-style-type: none"><li>• HDMI</li><li>• USB-C</li></ul>
Video Output Support	<ul style="list-style-type: none"><li>• HDMI</li><li>• USB-C</li></ul>
Video Resolution	<ul style="list-style-type: none"><li>• 1080p</li><li>• 4K</li><li>• 4K @ 30Hz</li><li>• 4K @ 60Hz</li></ul>

## Certifications & Warranties

Certifications	<ul style="list-style-type: none"><li>• NDAA 889</li><li>• Prop 65</li><li>• REACH</li><li>• RoHS</li><li>• TSCA</li></ul>
Data Transfer Rate	10 GBPS
Jacket Material	PVC
Warranty	Lifetime

Source: [https://www.legrandav.com/products/cables\\_and\\_connectivity/usb\\_cables/usb-c-to-hdmi-audiovideo-adapter-cable-4k-60hz/cg26896](https://www.legrandav.com/products/cables_and_connectivity/usb_cables/usb-c-to-hdmi-audiovideo-adapter-cable-4k-60hz/cg26896)