



kramer

WM-6P

6.5" Two-way Wall Mounted Passive Speaker

| Speakers



The WM-6P wall mounted passive speaker deliver exceptional sound performance for commercial indoor applications. The WM-6P is a high-end 6.5" wall mounted passive speaker featuring exceptional sound, optimized for conferencing and background music. The speaker supports both 8Ω low impedance as well as several 70V/100V high impedance modes. The speaker is supplied with Kramer's EasyMount mounting bracket for horizontal and vertical installations as well as for installation in corners, in addition the speaker has standard 75mm VESA mount threads for additional installation options. The speaker is available in both black & white colors

FEATURES

- Premium sound with high SPL
- Low-impedance (8Ω) / high-impedance (70V/100V)
- Power ratings: 30W continuous / 45W peak
- Sensitivity (1W@1m, free field): 90dB SPL
- Maximum SPL (@1m): Continuous 104dB SPL / Peak 106dB SPL
- UL1480A certified for indoor installations
- Industrial design: hidden wall-mount bracket for horizontal, vertical and corner installation, standard 75mm VESA mount threads, removable logo, available in black & white colors
- Eco-friendly mono-material packaging
- Included in the Box - 1 speaker (single unit), 2 speakers are packed in a single master box
- 1 EasyMount mounting bracket
- 4-pin pluggable Euroblock connector, 28-12AWG
- L-shaped Allen key (M6)
- Quick Start Guide



kramer

TECHNICAL SPECIFICATIONS

DESCRIPTION: Premium 6.5" two-way wall mounted passive speaker. Available in black & white colors

Audio

Driver:

LF Driver: 165 mm (6.5") driver with polypropylene cone and rubber surround

HF Driver: 25mm (1") soft dome with dampening, ferrofluid- cooled

Frequency characteristics

Frequency Range (-10dB): 60Hz-20kHz

Frequency Response (± 3 dB) 84Hz-20kHz

Dispersion angle: 132 deg. (1 kHz to 4 kHz)

Power ratings

@ 8 Ω Low impedance: 30W continuous / 45W peak

@ 100 V High impedance: 30W/15W/7.5W

@ 70 V High impedance: 30W/15W/7.5W/3.8W

Sound Pressure Level (SPL)

Sensitivity (1W@1m, free field) 90dB SPL

Maximum SPL: Continuous: 104dB SPL / Peak: 106dB SPL

MECHANICAL

Installation

Type: Surface mounted vertical, horizontal or in corners

Mounting: EasyMount bracket included, standard 75mm VESA mount threads

Connectors: 4-pin pluggable Euroblock connector, 28-12AWG

Weight per single speaker (including mounting bracket): 3.7kg (8.2lbs)

Dimensions

Dimensions without Bracket: 200mm x 182mm x 310mm / 7.17" x 6.63" / 12.2"

Dimensions with Bracket: 200mm x 246mm x 310mm / 7.17" x 9.67" / 12.2"

Shipping

Packed as single, 2 single boxes are packed in a master box

Shipping Dimensions (single unit): 342mm x 292mm x 400mm / 13.5" x 11.5" x 15.8"

Shipping dimensions (2 units in a Master box): 592mm x 352mm x 418mm / 23.3" x 13.9" x 16.5"

Shipping weight (single unit): 4.50Kg / 9.92lbs

Shipping weight (2 units in a Master box): 9.7Kg / 21.4lbs

Material

Grill: Powder Coated Steel, removable logo

Baffle: V-0 Flame Retardant

Bracket: Aluminium

Environmental

Operating Temperature: -5° to +50°C (23° to 122°F)

Storage Temperature: -10° to +55°C (14° to 131°F)

Humidity: 30% to 85%, RHL non-condensing

REGULATORY

UL1480A Certified: Meets safety standards for fire-protective signaling in commercial spaces

Environmental
: RoHS, REACH, WEEE

In the Box

1 speaker (single unit), 2 speakers are packed in a single master box
1 EasyMount mounting bracket
4-pin pluggable Euroblock connector, 28-12AWG
L-shaped Allen key (M6)
Quick Start Guide