



KT-2010-Gen2

10-Inch Wall / Table Mount PoE Touch Panel



KT-2010 is a new powerful, 10-inch, IPS, multi-touch, touch panel with 1920x1200 resolution. Elegantly designed for decorative room integration, this portable touch panel can be deployed either on a tabletop / wall. KT-2010, with the latest Android 13, supports wired PoE (Power over Ethernet) and advanced Wi-Fi connectivity options. The touch panel has a built-in speaker and camera and comes either with a tabletop or a wall mount. The touch panel is easy to assemble, using elegant wiring, secured mounting, reliable operation and flexible deployment. KT-2010 is a touch panel that is ideal for any 24/7 Kramer-supported commercial AV or control application and features a user-friendly, fully customizable graphical user interface configured by Kramer software

FEATURES

Elegant Design - Smooth integration with room furniture design, either on table or wall, with flexible panel cabling and locking design options

Superior User Experience - IPS 1920x1200 hi-resolution screen with $\pm 80^\circ$ horizontal and vertical wide viewing angles, ambient light sensor, proximity sensor, with advanced multi-touch points and 2-finger gesture capabilities

Powerful Processing - Genio 510 Hexa Core, LPDDR4 4GB RAM, 32GB eMMC (flash) processing performance, smoothly running complicated media and graphics-rich applications, such as H.264, H.265, video, audio streams encoding and decoding, and seamless hi-resolution 1x 13MP FF camera operation

Flexible Services - Latest Android 13 operating system

Easy Installation - Powering and connectivity via a single Ethernet cable

Flexible Mounting - Including table / wall mounts

Optional Connectivity - Simple wireless Bluetooth 5 as well as connection to USB peripheral devices for either table / wall-mount installations, using the included USB cable

Reliable Networking - Seamless switching between wired and wireless 802.11ac connectivity

Versatile Powering Options - PoE and power adapter (sold separately)

Auto Sensing - Optimized performance and operation according to automatically detected LAN speed

Firmware Update - Define automatic updates on a predefined time of the day or update manually using USB port

Secured Operation - Highly secured operation of applications using password protection, hidden control buttons and more. Red LED alert when camera is active

Secured Deployment - Flexible locking options to prevent unwanted panel mount removal, elegantly designed to remain out of site



TECHNICAL SPECIFICATIONS

Ports	1 Ethernet: On an RJ-45 female connector, 10/100/1000M with PoE 802.3at 1 USB Type C: On a female (OTG/ADB) connector 1 USB Type A: On a female connector
General	Operating System: Android Version 13 CPU Performance: Genio 510 Hexa Core RAM: LPDDR4 4GB Internal Storage Memory: 32GB eMMC (flash) Wireless Communication: Wi-Fi 6, 802.11 a/b/g/n/ax Bluetooth: BT 5.2 Display Screen: Capacitive multi-touch Display Size 10.1" Resolution 1920x1200 RGB pixels, 16:9 aspect ratio, >350cd/m2 brightness, 1000:1 contrast ratio VESA Mounting Ready: Metal-fittings mounting screw holes for 75x75mm VESA mount Side-light Can indicate room status (requires 3rd party integration)
Audio	Speakers: 2 built-in x 1.5W Microphone: 2, Built-in Codecs: MPEG/OGG/AAC
Video	Camera: 1x 13MP FF Video Format: H.264, H.265, VC-1, MPEG-4, VP8, VP9 Image Codecs: JPEG/BMP/GIF/PNG
Power	PoE: 44 to 57V DC 0.6A complies with IEEE802.3af and IEEE802.3at PoE standards Optional power adapter: 12V DC 1.5 A Note: Operating Temperature: 0~40°C
Controls	Function button: On top Reset button: On top, recessed Factory reset button: On back, recessed
Accessories	Included: Power adapter Table-top mount, On Wall mount and screws Option: Power adapter
Environmental Conditions	Operating Temperature & Humidity: 0° to +40°C (32° to 104°F), 5% to 85% Storage Temperature & Humidity: -20° to +60°C (-4° to 140°F), 5% to 90%
Regulatory Compliance (Standards)	Safety: CE, FCC, UKCA

Compliance)

Environmental: RoHs, WEEE

PHYSICAL

Product Dimensions: W, D, H 242 x 21 x 173mm (9.5 x 0.8 x 6.8in)

Touch panel table top stand: W,D,H 131 x 111 x 98mm (5.1 x 4.3 x 3.8in)

Wall mount: (W, D, H) 120 x 115 x 11mm (4.7 x 4.5 x 0.4in)

Package Dimensions: W, D, H 309 x 242 x 175mm (12 x 9.5 x 6.8in)

Touch panel Weight: 482g (1lb)

Touch panel stand Weight: 300g (0.6lb)

KT-2010WM Package Weight: 1.4kg approx. (3.08lb)