



VIA CONNECT 3

Compact & Secure 4K Wireless Presentation and Collaboration Solution

| HDMI | Ethernet - RJ-45 | 4K/30 UHD



VIA CONNECT 3 is super-compact (9x9cm) and flexible to install, with both built-in Wi-Fi and LAN connectivity and includes industry-leading 1024-bit encryption for secure use on the internal network. VIA CONNECT3 gives iOS, Android, Chromebook, PC, and Mac users instant wireless connectivity with 4K advanced presentation capabilities. The product features content streaming with crystal-clear mirrored images and stunning video playback and includes iOS mirroring via AirPlay™, Windows & Android mirroring via Miracast™, as well as Chromebook mirroring

FEATURES

3rd party Security Certification

Built-In isolated Wi-Fi and LAN

Quick and Reliable Wireless Connectivity - A simple and intuitive user interface enables iOS, Android, Chromebook, PC, and Mac device users to instantly connect to a main display without a dongle. 2.4GHz/5GHz Wi-Fi and MIMO antennas establish and maintain a fast and reliable connection

Clientless Connectivity - Airplay, Miracast, join through browser

High Quality Video Streaming - Supports up to 4K resolution (using the VIA app Multimedia feature)

Optimized for Video Conferencing - Room devices driver feature allows users to wirelessly connect to the professional grade camera and AV in their meeting spaces easily and instantly

Calendar widget on the wallpaper for instant connectivity within one click

3rd Party Web Applications - Run directly from the device without needing to use the application

Powerful Security Feature - 802.1x User authentication, 1024-bit encryption, dynamic room code

Comprehensive Collaboration Functionality - Whiteboard, filesharing, View Main Display, chat, etc

Simultaneous Display - Four participants can simultaneously present content on the main display

Seamless Live Video Streaming - Stream live content from meeting rooms, classrooms and studios using RTMP/RTMPS to all the leading platforms, like YouTube™, Kaltura™, Panopto™ and more

Easy and Flexible Installation - With a super-compact 9x9cm form factor, it can be discreetly installed on the back of a display, projector or almost anywhere

Up to 4K@30 HDMI Wired Input - Enables hard-wiring and auto-switching for connecting computers, cameras, multimedia players, or other HDMI-compatible devices. Note: This input does not support HDCP-protected content

Wireless USB - Supports Microphone, Speaker & Camera

Cloud-Based Management - Seamlessly compatible with VIA Site Management (VSM)



TECHNICAL SPECIFICATIONS

Ports	1 Ethernet: On an RJ-45 connector 3 USB 3.0: On a female USB type-A connector
Outputs	1 HDMI: 2.0 On a female HDMI connector
Control	Management VSM on Cloud
Video	Max Resolution Up to 4K@30Hz for both Input & Output Web Conferencing Cameras Tested with VIA Versa Feature Logitech MeetUp, Logitech C270, Logitech BCC950, Logitech C525, Logitech Brio UHD PRO, Logitech C310, Logitech C922, Avaya HC020, Avaya HC050, Huddly GO, Minrray MG100A, Microsoft Livecam HD-3000, TedGem 1080p, Vaddio HuddleSHOT, Yealink UVC80, Bose Videobar VB1, BIAMP Devio SCR-20, BIAMP Devio SCR-25, LUMENS B10U, LUMENS B11U, LUMENS B2U, MAXHUB — UCS10, Aver CAM340+, Aver VB342+, Yealink UVC30ROOM, Aver CAM340+, Avonic AV-CM44-VCUC-B PTZ, Konftel C50 PTZ Video Conferencing Apps Tested with VIA Versa Feature Teams and Zoom All brand names, product names, and trademarks are the property of their respective owners
General	Networking: 1 x Gigabit LAN Wi-Fi 802.11 ac/b/g/n dual band & Bluetooth Operating System: Linux
Power	Source: 12V DC Consumption: 3.8A
Accessories	Included: Power adapter
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Regulatory Compliance (Standards Compliance)	Safety: CE, FCC, UL, BIS
Enclosure	Type Aluminium cooling, fan with sink, Kensington lock Dimensions 89.9mm x 89.9mm x 36mm (3.54" x 3.54" x 1.42")
Product Dimensions	9.00cm x 9.00cm x 3.40cm (3.54" x 3.54" x 1.34") W, D, H
Product Weight	0.3kg (0.6lbs) approx
Shipping Dimensions	15.70cm x 12.00cm x 11.00cm (6.18" x 4.72" x 4.33") W, D, H
Shipping Weight	0.9kg (2.0lbs) approx



